

Technical data sheet

Nominal capacity (based on suction conditions 1 bar (a), 20°C)

Volume flow inlet	5250 m ³ /h
Volume flow outlet	5250 m ³ /h
Average regeneration air	0 m ³ /h
Compressed air inlet temperature	40°C
Ambient temperature	25°C
Working pressure	7 bar (g)
Pressure dew point	-40°C

General data

Maximum operating pressure	11 bar (g)
Minimum operating pressure	4 bar (g)
Maximum inlet temperature	40°C
Ambient temperature minimum	2°C
Ambient temperature maximum	35°C

Cycles

Adsorption time-dependent	rigid 360, variable max 720
Adsorption load-dependent	480 minutes (option dew point control TPS required)
Regeneration: Expansion	rigid 20, variable 20
Regeneration: Heating phase (at least)	rigid 165, variable 165
Regeneration: Cooling phase (at least)	rigid 50, variable 50
Pressure build-up timet	rigid 15, variable 15

Electrical data

Electric power heater	48 kW
Electric power vacuum pump	15 kW
Electric power control	0,2 kW
Average heater power time-dependent	33,77 kW/h
Average heater power depending on load	27,17 kW/h (option dew point control TPS required)
Medium vacuum pump power time dependent	8,99 kw/h
Medium vacuum pump power load dependent	7,23 kw/h (option dew point control TPS required)
Electrical connection	400
Frequency	50 Hz
Maximum protection	3 x 150 Ampere
Degree of protection switch cabinet	54

Norms and key figures

Testing pressure	16,5 bar g
Pressure vessel standard	2014/68/EU
Fluid group	2
Category	IV
Module	B+F
Sound insulation level	ISO 85

Head-generated adsorption dryer ATW-V 525

Rev 01_1118

Technical data sheet

Page 2 of 2

Dimensions and weights

A	3500 mm
C	2590 mm
D	1900 mm
Connection input	DN 150 PN 16
Output connection	DN 150 PN 16
Total weight	4280 kg
Vessel volume	1667 Liter
Connection of vacuum pump exhaust air	optionally DN 150 PN 6 (DIN 2631) or DN 150 PN 6 (DIN 24154 line 4)

Scope of supply

Ready-to-operate adsorption dryer	ATW-V 525
Controls	Control cabinet with Touch Panel Siemens, S7 (standard)
Filling	BASF KC Trockenperlen WS / N
Total weight of filling	1905 kg

Options

Dew point	TPS
Preliminary filter	ECOCLEAN FF150-04SMA
Afterfilter	ECOCLEAN FF150-04DMF
Connections filtration	DN 150
Insulation	about cylindrical length of the container, heater tube and pipe bridges below

Dimensional drawings

