

F314ST-F338ST-F312ST

Stainless steel AISI 316L filters,
suitable for gas and liquid



FEATURES

Filter for inlet pressure up to 50 bar (725 psi) in the standard version.

Inlet and outlet connections 1/4" – F, 3/8" – F and 1/2" – F.

Welded EN or ASME flanges available on request.

Stainless steel AISI 316L body from bar and drawn stainless steel AISI 316L bowl.

Filtration rate: 5 µm, 50 µm.

Condensation drain: automatic drain SAI for pressure up to 16 bar (232 psi), manual drain SM for pressure up to 30 bar (435 psi).

Available the ATEX 2014/34/EU version.

Brand $\text{CE} \text{ II 2 G c I I C T X}$

$\text{CE} \text{ II 2 D c I I I C T X}$.

For use in potentially explosive atmospheres zones: 1, 21, 2, 22 (not for mines and zone 0).

The product complies with the directive 2014/68/EU PED.

Available the EAC-EX TP TC 012/2011 versions for the Russian market.

Available units composed of:
Filter + Regulator + Lubricator

SPECIFICATIONS

Filter weight: F314 ST / F338 ST ~1.1 kg (~2.42 lb)

F12 ST ~2.1 kg (~4.63 lb)

Standard version operating temperature: -20 °C ÷ +60 °C (-4 °F ÷ +140 °F)

Degree of protection: IP56, IP66 for cap drain version

Bowl capacity F14 ST / F38 ST: 140 cc (4,7 US fl oz)

F12 ST: 200 cc (6,7 US fl oz)

Automatic drain SAI: drains the condensate before builds up to the filter cartridge (only for air version and PS=16 bar)

MATERIALS

Body: stainless steel AISI 316L

Bowl: stainless steel AISI 316L

Internal parts: stainless steel AISI 316L

Filter cartridge: stainless steel AISI 316L

O-Ring: FPM (alternative compounds available on request)

ACCESSORIES

Wall mounting bracket kit

SPARE PARTS

Filter cartridges

Complete kit: gaskets and filter cartridge

Manual drain (FPM o-ring)

Automatic drain (FPM o-ring)

generating the product code

Filtri serie ST in AISI 316L / AISI 136L Filter series ST			
AA BB CC D E FF			
AA	Attacchi / Connections	L0	3/8"G-F
		N0	1/4"G-F
		P0	1/2"G-F
BB	Tipologia di fluido / Fluid type	15	O2
		97	NBR
		98	EPDM
		99	FPM
CC	Tazza + scarico / Bowl + drain	31	SAI / Automatic drain 16bar
		32	SM / Manual drain 30bar
		33	Tappo / Cap 50bar
D	Filtrante / Filter	C	5µm
		H	50µm
E	Marchiato / Marked	I	Insert Deal
		Z	Dir. ATEX 2014/34/EU
FF	Accessori / Accessories	00	Nessun accessorio
		06	Manometro / Pressure gauge

CODE COMPOSITION EXAMPLE

233# H0 97 31 J I 00

233#: Series ST filter

H0: Connections 1/2 NPT

97: NBR o-ring

31: Automatic drain, PS=16 bar (232 psi)


C: Filtration rate 5 µm

I: Insert Deal

00: No accessories

technical drawings (all dimensions in mm)

Bracket to be ordered separately, kit order number: M13001




PS bar	DRAIN	L
16	AUTOMATIC	~154,5
30	MANUAL	~148
50	NO DRAIN	~140
80	NO DRAIN	~140

TYPE	IN/OUT	BODY MATERIAL	BOWL MATERIAL
F314ST GAS	G1/4-F	AISI 316L	AISI 316L
F338ST GAS	G3/8-F	AISI 316L	AISI 316L
F314ST NPT	1/4"NPT-F	AISI 316L	AISI 316L
F338ST NPT	3/8"NPT-F	AISI 316L	AISI 316L

GAS FILTRATION	
CARTRIDGE	MATERIAL
5 µm	AISI 316L
5 µm	PE
50 µm	AISI316L

technical drawings (all dimensions in mm)



PS [bar]	DRAIN	L
16	AUTOMATIC	~165
30	MANUAL	~158
50	NO DRAIN	~150
80	NO DRAIN	~150

TYPE	IN/OUT	BODY MATERIAL	BOWL MATERIAL
F312ST G1/2"	G 1/2"-F	AISI 316L	AISI 316L
F312ST 1/2"NPT	1/2" NPT-F	AISI 316L	AISI 316L

GAS FILTRATION	
CARTRIDGE	MATERIAL
5 µm	PE
5 µm	AISI 316L

ID Insert Deal Srl

Strada dei Boschi, 40
20852 Villasanta (MB) Italia
tel. +39 039 302035
info@idinsertdeal.com
www.idinsertdeal.com

ID Insert Deal si riserva il diritto di cambiare le specifiche del prodotto senza preavviso.
ID Insert Deal reserves the right to change and/or modify product specifications without prior notice.

Insert Deal non si assume alcuna responsabilità per la scelta, uso e manutenzione di qualsiasi prodotto. La responsabilità per l'ideale scelta, uso e manutenzione di qualsiasi prodotto ID rimane interamente a carico dell'acquirente.
Insert Deal does not assume responsibility for selection, use and maintenance of any products. Responsibility for proper selection, use and maintenance of any ID products remains entirely to the purchaser.

Riproduzione vietata. Tutti i diritti riservati; nessuna parte del presente documento può essere riprodotta senza autorizzazione di ID Insert Deal Srl.
Reproduction forbidden. All rights reserved; the hereby document can't be reproduced, also partially, without the authorization of ID Insert Deal Srl.

FILTER_233(F314ST-F338ST-F312ST)_EN_02



Azienda con sistema di gestione qualità certificato.
certificato N° 50 100 9191
Company with certificated quality management system.
certificate N° 50 100 9191