



CLEAN



COOL



**CONVEY** 



VAFIBLAST Safety Air Guns..... pg. 99

Sanitary Flange Line Vac™......pg. 152

G374 Static Eliminators.....

CATALOG

OU REQUESTED THIS CATALOG AND PRICE LIST. PLEASE SEE MAILING LABEL ON BACK COVER.

Stay up to date by visiting our website and take advantage of the information and services we didn't have room to display in this catalog.



The digital home of Intelligent Compressed Air® products for industry



#### Where you can

- Chat live with our problem solving, technical expert Application Engineers
- Watch product videos to learn more about the features and benefits of our engineered products
- Quickly order online with a purchase order or credit card (US & Canada)
- Access product presentation slides you can use to educate others
- Find International Distributors all across the world



#### **Access our Knowledge Base to**

- Download 3D models and CAD drawings in multiple formats to place into your drawings
- Calculate air savings and ROI to see how quickly EXAIR products will pay off
  - Search our Case Study Library & Applications database and become familiar with how our products solve problems
- Use our product FAQ's for quick access to our most common questions
- Learn about our free Efficiency Lab service and use it to determine air and money savings you can achieve when installing EXAIR engineered solutions
- Collect compressed air data and pipe sizing recommendations
- Find Flow, Force and Heat conversions



#### Visit our PDF library and download

- · Electronic files of the entire catalog or individual sections
- Installation and Maintenance Guides on every EXAIR product
- Our current **price list** to have all product prices in one convenient location
- EXAIR's Air Nozzle Blowoff Guide to see the details on our enormous selection
  of sizes, materials and performance options



#### Follow our blog for 5 new entries a week and learn

- Details and installations of widely varied applications
- The methodology and results of critical mathematical formulas which help determine money savings, air savings, performance benefits and more
- New product releases before they reach our catalog or website
- More about EXAIR, our team and community involvement
- Go to blog.exair.com

#### Make social connections

- Watch over 90 videos on EXAIR's YouTube Channel and see product features and benefits, applications, Tips & Tricks, How-to, our team members, or be entertained by Professor Penurious!
- Follow our Company on Twitter @EXAIR or our Application Engineers and learn more about
  promotions, updates on manufacturing, engineering and international industry perspective.

















f Q+



Connect with us on Facebook at facebook.com/exair or follow us on Google+

Terms and Conditions 4 Efficiency Lab 5 Standards Compliance
EXAIR Optimization  Minimize compressed air use and detect wasteful leaks 6 Steps to Optimization
Air Knives  Blowoff, clean, dry and cool with less noise and air consumption  Super Air Knife
Air Wipes Blowoff, dry, clean and cool pipe, cable, extruded shapes and hose Standard Air Wipes. 36 Standard Air Wipes. 40
Air Amplifiers  Vent, exhaust, cool, dry and clean-with one moving parts  Super Air Amplifiers

Adjustable Air Amplifiers......48

50	

	les and	

Reduce noise levels and air costs on blowoff operations

Air Nozzles
Air Nozzle Comparison Chart52
Super Air Nozzles
Flat Super Air Nozzles55
Back Blow Air Nozzles57
Safety Air Nozzles
Air Jets59
High Force Air Nozzles61
High Force Air Nozzle Comparison Chart61
High Force Flat Super Air Nozzles
High Force Super Air Nozzles61
Super Air Nozzle Clusters65
Stay Set Hoses
Swivel Fittings66
Blowoff Systems

AL	omizing Nozzies
	stainless steel construction for durability d corrosion resistance
131/2	1/8 NPT Atomizing Nozzles68
13102	Internal Mix Narrow Angle Round
	Atomizing Nozzles
	Internal Mix Wide Angle Round
	Atomizing Nozzles
	Internal Mix Flat Fan Atomizing Nozzles
	External Mix Narrow Angle Flat Fan
	Atomizing Nozzles
	Siphon Fed Round Atomizing Nozzles73
	Siphon Fed Flat Fan Atomizing Nozzles74
	1/4 NPT Atomizing Nozzles75
	Internal Mix Narrow Angle Round
	Atomizing Nozzles
	Internal Mix Wide Angle Round
	Atomizing Nozzles
	Internal Mix Flat Fan Atomizing Nozzles
	Internal Mix Deflected Flat Fan
	Atomizing Nozzles
	Internal Mix 360° Hollow Circular
	Atomizing Nozzles
	External Mix Round Atomizing Nozzles 79
	External Mix Narrow Angle Flat Fan
	Atomizing Nozzles
	External Mix Wide Angle Flat Fan

Atomizing Nozzles continued	
Siphon Fed Round Atomizing Nozzles	.82
Siphon Fed Flat Fan Atomizing Nozzles	.8.
1/2 NPT Atomizing Nozzles	.84
Internal Mix Narrow Angle Round Atomizing Nozzles	. 84
Atomizing Nozzles	. 85
Internal Mix Flat Fan Atomizing Nozzles	
Atomizing Nozzles	. 8
External Mix Narrow Angle Flat Fan Atomizing Nozzles	. 88



#### No Drip Atomizing Nozzles

Eliminate drips to conserve valuable liquids and improve product finishes.	
№ 1/8 NPT No Drip Atomizing Nozzles 9	0
2- No Drip Internal Mix Narrow Angle Round Atomizing Nozzles	1
№ No Drip Internal Mix Wide Angle Round Atomizing Nozzles	1
P. No Drip Internal Mix Flat Fan Atomizing Nozzles	2
№ No Drip External Mix Flat Fan Atomizing Nozzles	
No Drip Siphon Fed Round Atomizing Nozzles 9- No Drip Siphon Fed Flat Fan Atomizing Nozzles. 9-	
1/4 NPT No Drip Atomizing Nozzles9	1
No Drip Internal Mix Narrow Angle Round Atomizing Nozzles	
No Drip Internal Mix Wide Angle Round Atomizing Nozzles	1
No Drip Internal Mix Flat Fan Atomizing Nozzles	2
No Drip Internal Mix Deflected Flat Fan Atomizing Nozzles	2
No Drip Internal Mix 360° Hollow Circular Atomizing Nozzles	2
No Drip External Mix Round Atomizing Nozzles	3
No Drip External Mix Narrow Angle Flat Fan Atomizing Nozzle	3
No Drip External Mix Wide Angle Flat Fan Atomizing Nozzle	
No Drip Siphon Fed Round Atomizing Nozzles 9- No Drip Siphon Fed Flat Fan Atomizing Nozzles 9-	
1/2 NPT No Drip Atomizing Nozzles 9	1
No Drip Internal Mix Narrow Angle Round Atomizing Nozzles	
No Drip Internal Mix Wide Angle Round Atomizing Nozzles9	1
No Drip Internal Mix Flat Fan Atomizing Nozzles9. No Drip Internal Mix 360° Hollow Circular	2
Atomizing Nozzles	

No Drip Siphon Fed Round Atomizing Nozzles...94 Droplet Size/Spray Angle Information .......95



MANUFACTURING INTELLIGENT COMPRESSED AIR® PRODUCTS SINCE 1983

9	5	
	V	

Safety	v Air	Guns

Safety air guns use engineered air nozzles for high performance

	Chip Shields	.97
	Precision Safety Air Guns	.98
THE R	VariBlast Compact Safety Air Guns	.99
	Soft Grip Safety Air Guns	101
	Heavy Duty Safety Air Guns	104
	Back Blow Safety Air Guns	105
	Super Blast Safety Air Guns	106



#### Static Eliminators

shock hazard
Gen4 Super Ion Air Knife110
Static Meter
☑️🏧 Gen4 Standard Ion Air Knife
₩∰ Gen4 lonizing Bars118
Gen4 Super Ion Air Wipes120
Gen4 Ion Air Cannon122
Gen4 Ion Air Gun124
Gen4 Ion Air Jet/Gen4 Stay Set Ion Air Jet126
Gen4 Ionizing Point128
Gen4 Power Supplies

#### E-Vac® Vacuum Generators

Vacuums for lifting, clamping, mounting and placement

How to Build an E-Vac System131
In-Line
Adjustable
Vacuum Cups



#### Air Operated Conveyors

Convey parts, materials and waste with no moving parts

Line Vac	141
Threaded Line Vac	147
Heavy Duty Line Vac	150
- Sanitary Flange Line Vac	152
Light Duty Line Vac	154
	Threaded Line Vac



#### Industrial Housekeeping

Reliable vacuums for chip removal, liquid transfer and cleaning

Reversible Drum Vac1	56
High Lift Reversible Drum Vac1	58
Chip Trapper1	60
High Lift Chip Trapper	62
Chip Vac	64
Heavy Duty Dry Vac1	
Heavy Duty HEPA Vac1	68
Vac-u-Gun1	70
Deep Hole Vac-u-Gun	72



#### Vortex Tubes & Spot Cooling ■

Cold air for industrial spot cooling problems Vortex Tubes .......174 Adjustable Spot Cooler......182 

1	8	5

#### Cold Gun Aircoolant Systems

Cool machining operations with clean, cold air

#### Cabinet Cooler® Systems

Cool and purge NEMA 12, 4 and 4X electrical

itroi paneis
How it Works19
Selecting the Right Model19
Special Duty Cabinet Coolers19
Calculating Heat Load194
Cabinet Cooler Sizing Guide
NEMA 12 Models19:
NEMA 4 Models198
NEMA 4X Models19
Cabinet Cooler System Accessories 20



### Mufflers, filters, regulators, valves, swivel

fittings and more

Filters201
Regulators
Silencing Mufflers
Valves, Swivels, Thermostats 205
Magnetic Bases, Stay Sets, Hoses
Air Hoses
Fittings
Receiver Tank



Catalog item orders received before 3 pm EDT/ EST are generally shipped from Cincinnati, Ohio on the same day. You can expect delivery within 1-4 days depending on your location.

### Terms and Conditions (U.S. and Canada Only)

Terms: Net 30 days upon credit approval, Visa, MasterCard, Discover and American Express.









#### ICC (International Chamber of Commerce) INCOTERM 2010:

EX WORKS (EXAIR Corporation, 11510 Goldcoast Dr., Cincinnati, Ohio 45249, USA.)

All cataloged products are shipped from stock, via U.P.S. within 24 hours after receipt of order. Delivery Priority shipment is available upon request.

Call 1-800-903-9247 or +1-513-671-3322 Worldwide 8:00 a.m. to 5:00 p.m. ET (Mon. - Fri.) Orderina:

Fax toll free 1-866-329-3924 or +1-513-671-3363 Worldwide

E-mail: orders@exair.com www.exair.com (secure web site)

Remit to address (payments only): **EXAIR Corporation** Location 00766, Cincinnati, Ohio 45264-0766

Sales and use tax, where applicable, are not included.

Technical Assistance: Please call our Application Engineering Department, 1-800-90-EXAIR (1-800-903-9247), or e-mail at techelp@exair.com.

Built to Last WARRANTY

Warranty: 5 Year "Built To Last" Warranty against defects in workmanship and materials on all compressed air products\*. Defective products must be returned freight prepaid for repair or replacement at our \*5 Year Warranty applies to compressed air products only A 1 Year Warranty applies to all accessories and electrically option. This warranty applies under conditions of normal use, but does not apply to defects that powered products

**EXAIR's Unconditional Guarantee:** 

result from intentional damage, negligence, unreasonable use, wear or exposure. EXAIR unconditionally Extends to all U.S. and Canadian customers and includes

invoiced U.P.S. Ground Service shipping charges. Products returned after the 30 day guarantee period are subject to a 15% restocking charge. Products must be returned freight prepaid.



**Copyright Restrictions:** 

The content of the EXAIR Catalog, including all photos, graphics, drawings and arrangements are proprietary to EXAIR Corporation and are protected by the United States and international copyright and trademark laws. You are authorized to use the contents of the EXAIR Catalog for personal use or as it relates to your role as a current or prospective customer of EXAIR. The contents of this catalog may not be copied or modified for any type of publication or distribution without the prior written consent of EXAIR Corporation. The content of the EXAIR Catalog is the intellectual property solely of the EXAIR Corporation with no rights transferred to other parties. No part of this catalog may be reproduced for any commercial purposes without the express authorization in writing by the EXAIR Corporation.

Trademarks:



11510 Goldcoast Dr.

Cincinnati, Ohio 45249-1621 Phone Number: (513) 671-3322 Fax Number: (513) 671-3363 E-mail: techelp@exair.com Web Site: www.exair.com

"EXAIR.com", "EXAIR", "Cabinet Cooler", "E-Vac", "Intelligent Compressed Air", and "Compressed Air Intelligence" are registered trademarks of the EXAIR Corporation. The EXAIR logo, product names, designs and descriptive phrases are trademarked by EXAIR Corporation. These trademarks may not be used without prior written permission of the EXAIR Corporation.

EXAIR Logger, VariBlast, Gen4, EFC, Digital Flowmeter, Digital Sound Level Meter, High Power Cold Gun, Super Air Knife, Standard Air Knife, Full-Flow Air Knife, Air Cannon, Super Air Amplifier, Adjustable Air Amplifier, Super Air Nozzle, Micro Air Nozzle, High Power Safety Air Nozzle, Stay Set Hose, Super Blast Safety Air Gun, Super Air Wipe, Standard Air Wipe, Super Ion Air Knife, Standard Ion Air Knife, Super Ion Air Wipe, Ion Air Cannon, Ion Air Gun, Ion Air Jet, Ionizing Point, Stay Set Ion Air Jet, Line Vac, Chip Vac, Heavy Duty Dry Vac, Heavy Duty HEPA Vac, Reversible Drum Vac, High Lift Reversible Drum Vac, Chip Trapper, High Lift Chip Trapper, Vac-u-Gun, Deep Hole Vac-u-Gun, Air Disk, Air Stik, Mini Cooler, Cold Gun Aircoolant System, and ETC are trademarks of EXAIR Corporation.



Intelligent Compressed Air® products are identified throughout this catalog that can help your plant save tens of thousands of dollars over the course of a single year. The Best Practices for Compressed Air Systems manual published by the Compressed

Air Challenge\* recommends products like the Super Air Knife", Super Air Amplifier", and the family of Super Air Nozzles™ for energy conservation. Many of the products shown offer unique ways to solve common industrial problems using compressed air. Compressed Air Challenge is a registered trademark of Compressed Air Challenge, Inc.



EXAIR has partnered with Energy Star, a voluntary program of the U.S. Department of Energy and the Environmental Protection Agency. Energy Star offers energy efficient solutions to help save money while protecting the environment for future generations. EXAIR has implemented improved energy management practices and technologies throughout our facility, including energy efficient lighting, HVAC systems, and electronic thermostats. EXAIR's participation in this program underscores our commitment to conserving energy.

EXAIR products are subject to ongoing development. Specifications are subject to change without notice. Some products in this catalog are covered by U.S. Patent #5402938, #8153001, #8268179, and #9156045, and others may be U.S. Patent Pending. Copyright @2017 EXAIR Corporation. All Rights Reserved.









Compressed Air® products vs Your current installation

How does the Efficiency Lab work?

Our Efficiency Lab service begins with receiving a sample of the product(s) you currently use for your application. One of our qualified Application Engineers will use calibrated testing equipment to compare the performance of your existing product(s) to an EXAIR engineered solution. These tests will determine air consumption, noise levels and force. The test results will then be published in a comprehensive report, which includes a cost savings analysis, and be provided to you. For most applications, EXAIR products can help you improve application efficiency AND typically pay for themselves in a matter of weeks.

#### How can I get a product tested for free?

To participate in our FREE Efficiency Lab please contact one of our Application Engineers and get the details about sending us your product(s).

You may reach an Application Engineer by phone at (800) 903-9247 or (513) 671-3322. You can send an email to lab@exair.com or visit our website and take advantage of our live help at www.exair.com.

EXAIR's FREE Efficiency Lab service determines how much air and dollar savings you will achieve by installing one of our Intelligent Compressed Air products.

## Unable to send your product to EXAIR's Efficiency Lab?

If it is not possible to send us your product, we have a one page Product Efficiency Survey on our website (www.exair.com/labdoc.htm) where you can provide us the details about a current inefficient compressed air application. Fill in the information and click submit. You will hear from one of our Application Engineers within 3 business days.

#### Okay, so what is the fine print?

This service is available to all customers in the U.S. and Canada only. Some restrictions may apply.

#### What about confidentiality?

Yes, EXAIR will keep the results of our Efficiency Lab test and report confidential unless given permission to share that information with others.

Products must be shipped to EXAIR freight prepaid. EXAIR will pay the return shipping via UPS ground.





# **Safety Air Guns**

# Safety Air Guns use engineered air nozzles for high performance!

#### Why EXAIR Safety Air Guns?

Inexpensive air guns are sold through many catalogs and industrial supply companies. Most have triggers or other parts that break quickly. Their performance is similar to open pipe, where they simply blow a lot of compressed air. In addition to the high air consumption, many produce noise levels that violate OSHA requirements. Some even generate dangerous dead end pressures that can result in serious or fatal injuries if blocked.



EXAIR's Safety Air Guns eliminate these problems. They are durable and comfortable to use. Each model uses an engineered Air Nozzle that provides superior performance by entraining large volumes of surrounding air. Safe operation is assured along with low air consumption and noise levels. Airflow that exits the nozzle can not be blocked, as required by OSHA standard 1910.242(b).

#### **Selecting The Right Safety Air Gun**

The pages that follow show five Safety Air Guns. The Precision, VariBlast™, Soft Grip, Heavy Duty and Super Blast Safety Air Guns are available with a variety of air nozzles (listed in order of force). Stainless steel air nozzles provide more mechanical wear resistance while withstanding corrosion and high temperatures. PEEK Air Nozzles provide protection from accidental impact with the target and outstanding corrosion resistance. Air consumption, force and sound level are shown for all models. Complete details for each Air Nozzle are shown on pages 50-67.



**Precision Safety Air Gun** is extremely lightweight and the most comfortable to operate during periods of extended use. The small diameter nozzle and extension will fit into tight spaces while providing strong blowing force. Chip Shields for worker safety are also available.



VariBlast™ Compact Safety Air Gun is a uniquely powerful gun which produces variable force depending on trigger valve pressure. You decide how much force is needed for the application by squeezing the trigger a little or all the way for maximum force! This cast aluminum gun is equipped with any of our 1/8 NPT engineered air nozzles. The VariBlast Compact Safety Air Gun is small, comfortable and powerful while remaining light and ergonomic. Has two inlets for flexible air supply. Extension Pipes for hard to reach areas are also available.



**Soft Grip Safety Air Gun** has a durable cast aluminum body that is suited for rugged industrial use. The ergonomic design has a large trigger for easy operation and a convenient hanger hook for easy storage. Chip Shields for worker safety are available. Extension Pipes and Stay Set Hoses for hard to reach areas are also available.



**Heavy Duty Safety Air Gun** is a powerful air gun with a durable cast aluminum body that is best suited for heavy use in rugged industrial environments. The ergonomic composite rubber grip and wide curved trigger can be used for hours without fatigue. Chip Shields for worker safety are available. Extension Pipes for hard to reach areas are also available.



**Super Blast Safety Air Guns** provide the strongest blowing force - ideal for long distance, wide area blowoff, cooling, and drying applications. The comfortable foam rubber handle provides a firm grip. The spring-loaded valve instantly shuts off the air supply if the air gun is dropped. Extension Pipes for hard to reach areas are also available.







### **Chip Shields**

# Protect workers from flying debris and prevent splash back!

### Why the EXAIR Chip Shield?

Chip Shields are durable polycarbonate shields that protect operators from flying debris often associated with blowing chips off machined parts. Chip Shields are also great for keeping coolant from spreading everywhere during drying operations. EXAIR's Chip Shields help meet the requirements of OSHA 1910.242(b) for safe use of compressed air.

Chip Shields are available for EXAIR's Precision Safety Air Gun, VariBlast Compact Safety Air Gun, Soft Grip Safety Air Gun and Heavy Duty Safety Air Gun. Chip Shields can be used on Safety Air Guns with or without an Aluminum Extension. Chip Shields are not for use on guns that use a Stay Set Hose.



Model 1696SS-CS shown

Model 1360SS-CS shown

#### How to Order the EXAIR Chip Shield.

To order a Safety Air Gun with a Chip Shield, simply add a '-CS' to the end of the model number.

#### Examples:

**Model 1210-CS** is a Model 1210 Soft Grip Safety Air Gun with a Chip Shield.

Model 1310-12-CS is a Model 1310 Heavy Duty Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe and Chip Shield.

#### Chip Shields for Safety Air Guns With Aluminium Extensions

Chip Shields are also available to be retrofitted to existing Safety Air Guns. For models that already have an Aluminum Extension in place, the Chip Shield is supplied with a rubber grommet to ensure a tight fit onto the extension.

Chip Shield#	Safety Air Gun Models Covered					
901220	1408SS, 1408-PEEK, 1409SS, 1409-PEEK, 1410SS, 1410-PEEK					
901221	1229, 1229S, HP1229, HP1229SS, 1280SS, 1290S, 1290SS, 1296SS, 1296-PEEK, 1297SS, 1297-PEEK, 1298-SEK, 1299-PEEK, 1299, 1299SS, 1299-PEEK, 1690SS, 1696-PEEK, 1697SS, 1697-PEEK, 1698SS, 1698-PEEK, 1699, 1699-PEEK, 1699SS, 1629S, 1629SS, 1680SS, 1690, 1690SS, HP1629S, HP1629SP, 1629S, 1629SS, 1680SS, 1690, 1690SS, HP1629SP, 1629SP, 162					
901222	1210, 1210SS, 1210-PEEK, 1230, 1230SS, HP1230, HP1230SS, 1310, 1310SS, 1310-PEEK, 1330, 1330SS, HP1330, HP1330SS					
901223	1240, 1250, 1250SS, 1250-PEEK, 1260, 1260SS, 1340, 1350, 1350SS, 1350-PEEK, 1360, 1360SS					

#### Chip Shields for Safety Air Guns Without Aluminium Extensions

For models that **do not** already have an Aluminum Extension in place, a short extension nipple and the necessary adapter is provided.

Chip Shield Kit#	Safety Air Gun Models Covered
901231	1229, 12295, 1P1229, HP122955, 128055, 129055, 129055, 12965, 1296-FEK, 129755, 1297-PEKE, 129855, 1299-PEKE, 1299, 129955, 1299-PEKE, 169055, 1696-PEKE, 169755, 1697-PEKE, 169855, 1698-PEKE, 169955, 16295, 16295, 16295, 162955, 162055, 16205, 162055, 16205, 162055, 162
901232	1210, 1210SS, 1210-PEEK, 1230, 1230SS, HP1230, HP1230SS, 1310, 1310SS, 1310-PEEK, 1330, 1330SS, HP1330, HP1330SS
901233	1240, 1250, 1250SS, 1250-PEEK, 1340, 1350, 1350SS, 1350-PEEK
901234	1260, 1260SS, 1360, 1360SS



Model 1299-6-CS shown





#### Precision Safety Air Gun - 1/4 NPT Inlet

EXAIR's Precision Safety Air Guns are extremely lightweight and have a focused blast of air that provides excellent cleaning capability. The small diameter nozzle and extension easily fit into tight spaces while still packing a strong punch.

The Precision Safety Air Gun is available with EXAIR's Atto, Pico and Nano Nozzles, which were engineered to maximize entrainment of ambient air while minimizing air consumption and noise. Safe operation is assured since the airflow that exits the nozzle can not be blocked, as required by OSHA standard 1910.242(b). The 58 to 75 dBA noise level is well below the limits of the OSHA maximum allowable noise exposure standard 29 CFR 1910.95(a).

All nozzles are Type 316 stainless steel for superior corrosion resistance or PEEK plastic for non-marring applications and increased chemical resistance. The body is made of high impact, glass reinforced nylon. The inlet is 1/4 NPT. All models are available with an impact resistant polycarbonate Chip Shield.





Model 1408SS Nozzle: 1108SS Atto Super Air Nozzle Also Available: 1408-PEEK with 1108-PEEK PEEK Plastic Atto Super Air Nozzle

A Consur	ir mption	For	ce*	Sound Level
SCFM	SLPM	Ozs	Grams	dBA
2.5	71	2.0	57	58

Model 1409SS Nozzle: 1109SS Pico Super Air Nozzle Also Available: 1409-PEEK with 1109-PEEK PEEK Plastic Pico Super Air Nozzle

A Consu	Air Force* Sour		Force*	
SCFM	SLPM	Ozs	Grams	dBA
4.9	139	5.0	142	68

Model 1410SS

Nozzle: 1110SS Nano Super Air Nozzle Also Available: 1410-PEEK with

> 1110-PEEK PEEK Plastic Nano Super Air Nozzle

	Sound Level	Air Consumption		tion Force*		Sound Level
ıs	dBA	SCFM	SLPM	Ozs	Grams	dBA
	68	8.3	235	8.1	230	75











**Use Model** 900750

**Coiled Hose** 

### **VAFiBLAST**™ Compact Safety Air Guns



#### VAFiBLAST™Compact Safety Air Gun - 1/4 NPT Inlet

EXAIR's VariBlast™ Compact Safety Air Guns are a small and lightweight air gun capable of handling tough jobs. Designed with a variable flow trigger they are able to produce different force values from the same nozzle simply by pulling the trigger. These air guns can be outfitted with all of EXAIR's 1/8 NPT engineered air nozzles and extensions are available up to 72" long,

The wide variety of intelligent compressed air nozzles installed on the VariBlast Compact Safety Air Gun make it a great selection for light to medium duty applications requiring force values of up to 1 pound while remaining among the most efficient air guns in EXAIR's product line. EXAIR Super Air Nozzles are engineered to maximize entrainment of ambient air while minimizing air consumption and noise. Safe operation is assured since airflow that exits the nozzle can not be blocked, OSHA standard 1910.242(b). The 58 to 75 dBA noise level is well below the limits of the OSHA maximum noise exposure standard 29 CFR 1910.95(a).

Engineered air nozzles are available in Type 316 stainless steel for superior corrosion resistance and mechanical wear, Type 303SS for corrosion resistance, PEEK thermoplastic for nonmarring and chemical resistance or a zinc/aluminum alloy for general purpose applications. The air gun body is cast aluminum. Has two 1/4 NPT air inlets to ensure ergonomic handling. All models are available with an impact resistant polycarbonate Chip Shield.



Dual 1/4 NPT Air inlets



Model 1699 VariBlast Compact Safety Air Gun Nozzle: 1103 Mini Super Air Nozzle

	Air ensumption		Force*		1
SCFM	SLPM	Ozs	Grams	dBA	1
10	283	9	255	71	l





#### Model 1699SS VariBlast Compact Safety Air Gun Nozzle: 1103SS Stainless Steel Mini Super Air Nozzle

The Model 1699SS uses the stainless steel Super Air Nozzle constructed of Type 316 stainless steel for rugged use and corrosion resistance.



#### Model 1699-PEEK VariBlast Compact Safety Air Gun Nozzle: 1102-PEEK Plastic Mini Super Air

The Model 1699-PEEK uses the PEEK Super Air Nozzle for nonmarring and chemical resistance.

\*Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).




### **VAFiBLAST**™Compact Safety Air Guns



#### Model 1696SS

VariBlast Compact Safety Air Gun

Nozzle: 1108SS Stainless Steel Atto Super Air Nozzle Also Available: 1696-PEEK with 1108-PEEK PEEK Plastic Atto Super Air Nozzle



Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).



Use Model 900750 Coiled Hose




#### Model 169755

VariBlast Compact Safety Air Gun

Nozzle: 1109SS Stainless Steel Pico Super Air Nozzle

Also Available: 1697-PEEK with 1109-PEFK PEEK Plastic Pico Super Air Nozzle







#### Model 1698SS

VariBlast Compact Safety Air Gun

Nozzle: 1110SS Stainless Steel Nano Super Air Nozzle

Also Available: 1698-PEEK with 1110-PEEK PEEK Plastic Nano Super Air Nozzle

Air Consumption		Fo	rce*	Sound Level
SCFM	SLPM	Ozs	Grams	dBA
0.2	225	0.1	220	75







#### Model 1629

VariBlast Compact Safety Air Gun Nozzle: 1126 1" Flat Super Air Nozzle Also Available: 1629SS with 1126SS Stainless Steel 1" Flat Super Air Nozzle

.015" (0.38mm) shim installed

Air Consumption		Force*		Sound Level
SCFM	SLPM	Ozs	Grams	dBA
10.5	297	9.8	278	75



Use Model 900750 Coiled Hose



#### Model 1680SS

VariBlast Compact Safety Air Gun Nozzle: 1010SS Micro Super Air Nozzle

Air Consumption		Force*		Sound Level
SCFM	SLPM	Ozs	Grams	dBA
13	368	12	340	80



Use Model 900750 Coiled Hose



#### Model 1690

VariBlast Compact Safety Air Gun Nozzle: 1009 Adjustable Air Nozzle Also Available: 1690SS with 1009SS

Stainless Steel Adjustable Air Nozzle

Air Consumption		Force*		Sound Level
SCFM	SLPM	Ozs	Grams	dBA
13	368	12	340	79



Use Model 900750 Coiled Hose




#### Model HP1629

VariBlast Compact Safety Air Gun

Nozzle: HP1126 1" High Power Flat Super Air Nozzle Also Available: HP1629SS with HP1126SS Stainless Steel 1" High Power Flat Super Air Nozzle

₩ .025" (0.64mm) shim installed





900750



#### Model 1604SS-6-CS

VariBlast Compact Back Blow Safety Air Gun, 6" extension

Nozzle: 1004SS Stainless Steel Back Blow Air Nozzle Also Available: Models 1604SS-12-CS (12" ext.). 1604SS-24-CS (24" ext.), 1604SS-36-CS (36" ext.), with 1004SS Stainless Steel Back Blow Air Nozzle. Aluminum Extension and Chip Shield

Air Cons	umption	Sound Level	Use With:
SCFM	SLPM	dBA	Inside Diameter
4.5	127	75	1/4"-1" (6.3-25.4mm





#### **Add An Extension Pipe**

Add an Extension Pipe to your VariBlast Compact Safety Air Gun. Here's how:

- 1. Choose an EXAIR VariBlast Compact Safety Air Gun. Example: Model 1699
- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length after the model of the VariBlast Compact Safety Air Gun.

**Example:** The Model 1699 VariBlast Compact Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1699-12.

#### **Aluminum Extension Pipe** All VariBlast Compact Safety Air Guns with Extension Pipes come fully assembled.

Model Addition #	Length		
-6	6" (152mm)		
-12	12" (305mm)		
-18	18" (457mm)		
-24	24" (610mm)		
-36	36" (914mm)		
-48	48" (1219mm)		
-60	60" (1524mm)		
-72	72" (1829mm)		

### Chip Shields can be added to EXAIR's Safety Air Guns by adding a "-CS" to the Model #.



**Example:** 

1699 (VariBlast Compact Safety Air Gun) + -CS (Chip Shield)

1699 - CS











### **Soft Grip Safety Air Guns**



#### Soft Grip Safety Air Gun - 1/4 NPT Inlet

EXAIR's Soft Grip Safety Air Gun is ideal for hours of continuous use without fatigue. The ergonomic design keeps the hand in a comfortable position and incorporates a large trigger that permits operation with one or more fingers. The durable cast aluminum body is suited for rugged industrial use and includes a convenient hanger hook for easy storage. The Soft Grip Safety Air Gun is available with Air Nozzles as shown for quiet, safe and efficient use of the compressed air supply. Aluminum Extension Pipes, Stay Set Hoses, and Chip Shields are available for most models. The inlet is 1/4 NPT.







Model 1210SS SG Safety Air Gun Nozzle: 1100SST Super Air Nozzle

The Model 1210SS uses the stainless steel Super Air Nozzle constructed of Type 316 stainless steel for rugged use and corrosion resistance.



Air inlet

Model 1210-PEEK SG Safety Air Gun Nozzle: 1100T-PEEK Super Air Nozzle

The Model 1210-PEEK uses the PEEK Super Air Nozzle for non-marring and chemical resistance.

\*Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).



### **Soft Grip Safety Air Guns**



#### **Model 1299** SG Safety Air Gun

Nozzle: 1103 Mini Super Air Nozzle

Also Available: 1299SS with 1103SS Stainless Steel Mini Super Air Nozzle 1299-PEEK with 1102-PEEK PEEK Plastic Mini Super Air Nozzle

Air Consumption		Force*		Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
10	283	9.0	255	71	





#### Model 1229 SG Safety Air Gun

Nozzle: 1126 1" Flat Super Air Nozzle Also Available: 1229SS with 1126SS Stainless Steel 1" Flat Super Air Nozzle ₩ .015" (0.38mm) shim installed

Air Consumption		Force*		Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
10.5	297	9.8	278	75	





#### **Model 1290** SG Safety Air Gun

Nozzle: 1009 Adjustable Air Nozzle Also Available: 1290SS with 1009SS Stainless Steel Adjustable Air Nozzle

Air Consumption		Fo	rce*	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
13	368	12	340	79	





#### Model 1280SS SG Safety Air Gun

Nozzle: 1010SS Micro Air Nozzle

Air Consumption		Fo	rce*	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
13	368	12	340	80	





#### Model HP1229 SG Safety Air Gun

Nozzle: HP1126 1" High Power Flat Super Air Nozzle Also Available: HP1229SS with HP1126SS Stainless Steel 1" High Power Flat Super Air Nozzle

.025" (0.64mm) shim installed

Air	Air Consumption		Force*		Sound Level	
SC	FM	SLPM	Ozs	Grams	dBA	
1	7.5	495	16	454	82	







#### **Model 1230** SG Safety Air Gun

Nozzle: 1122 2" Flat Super Air Nozzle Also Available: 1230SS with 1122SS Stainless Steel 2" Flat Super Air Nozzle

.015" (0.38mm) shim installed

Air Consumption		Force*		Sound Level	
SCFM	SLPM	Ozs	Grams	dBA	
22	622	22	624	77	





102





#### **Soft Grip Safety Air Guns**



#### Model 1250 SG Safety Air Gun

Nozzle: 1104 3/8 NPT Super Air Nozzle Also Available: 1250SS with 1104SS 3/8 NPT Stainless Steel Super Air Nozzle 1250-PEEK with 1104-PEEK 3/8 NPT PEEK Plastic Super Air Nozzle

\* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).

Air Consumption		For	Sound Level	
SCFM	SLPM	Lbs	Grams	dBA
35	991	1.9	850	82



Model HP1230 SG Safety Air Gun Nozzle: HP1125

2" High Power Flat Super Air Nozzle

Also Available: HP1230SS with HP1125SS Stainless Steel 2" High Power Flat Super Air Nozzle ₩ .025" (0.64mm) shim installed

Air Cons	umption	For	ce*	Sound Level
SCFM	SLPM	Lbs	Grams	dBA
37	1,039	2.2	1,134	83



Model 1240 SG Safety Air Gun

Nozzle: 1111-4 Super Air Nozzle Cluster

Air Cons	umption	For	ce*	Sound Level
SCFM	SLPM	Lbs	Grams	dBA
56	1,585	3.2	1,451	82



#### Model 1260 SG Safety Air Gun

Nozzle: 1106 1/2 NPT Super Air Nozzle

Also Available: 1260SS with 1106SS 1/2 NPT Stainless Steel Super Air Nozzle

Air Consumption		For	Force*	
SCFM	SLPM	Lbs	Grams	dBA
60	1,699	3.3	1,497	87



#### Model 1204SS-6-CS

SG Back Blow Safety Air Gun

Nozzle: 1004SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield

Air Cons	umption	Sound Level	Use With:
SCFM	SLPM	dBA	Inside Diameter
4.5	127	75	1/4" - 1" (6.3-25.4mm)



Model 1206SS-6-CS SG Back Blow Safety Air Gun

Nozzle: 1006SS Stainless Steel Back Blow Air Nozzle. Aluminum Extension and Chip Shield

Air Cons	umption	Sound Level	Use With:
SCFM	SLPM	dBA	Inside Diameter
22	622	80	7/8" - 4" (22–102mm)

#### Add An Extension Pipe Or Stay Set Hose

Add an Extension Pipe or Stay Set Hose to your Soft Grip Safety Air Gun. Here's how:

#### 1. Choose an EXAIR Soft Grip Safety Air Gun. Example: Model 1210

- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length after the model of the Soft Grip Safety Air Gun. (See table to right) Example: The Model 1210 Soft Grip Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1210-12.
- 3. To add a Stay Set Hose, create the model number by adding a dash and number of the appropriate Stay Set Hose after the model of the Soft Grip Safety Air Gun. (See table to the far right) Example: The Model 1210 Safety Air Gun with a 12" (305mm) Stay Set Hose is a Model 1210-12SSH

### Aluminum Extension Pin All Soft Grip Safety Air Guns with

Extension Pipes come fully assembled.					
Model Addition # Length					
-6	6" (152mm)				
-12	12" (305mm)				
-18	18" (457mm)				
-24	24" (610mm)				
-36	36" (914mm)				
-48	48" (1219mm)				
-60	60" (1524mm)				
TO TOUR (4000 )					

All Soft Grip Safety Air Guns with Stay Set Hoses come fully assembled.

•	
Model Addition #	Length
-6SSH	6" (152mm)
-12SSH	12" (305mm)
-18SSH	18" (457mm)
-24SSH	24" (610mm)
-30SSH	30" (762mm)
-36SSH	36" (914mm)

Stay Set Hose not available with 1240, 1250, 1260, 1204SS and 1206SS models.



Example:

1210 (Soft Grip Safety Air Gun)

-CS (Chip Shield)







### **Heavy Duty Safety Air Guns**

#### Heavy Duty Safety Air Gun - 3/8 NPT Inlet

Model 1310 Heavy Duty Safety Air Gun Nozzle: 1100T Super Air Nozzle



EXAIR's Heavy Duty Safety Air Gun is a powerful air gun that delivers high force for use in rugged, industrial environments. The 3/8 NPT compressed air inlet increases the compressed air flow available to the Super Air Nozzle, resulting in higher force and flow than other air guns. The durable cast aluminum body includes an ergonomic composite rubber grip and wide curved trigger that makes it comfortable for hours of use without fatigue. Aluminum Extension Pipes and Chip Shields are available. (Stav Set Hoses are not available.)



Nozzle: 1100SST Super Air Nozzle Type 316 Stainless Steel Super Air

Nozzle for rugged use and corrosion

Sound Leve

dRA

77





Model 1310-PEEK HD Safety Air Gun Nozzle: 1100T-PEEK Super Air Nozzle PEEK Super Air Nozzle for nonmarring and chemical resistance.



# Nozzle:

#### Also Available:

SCEM SI PM

22 622

Air Consumption

1330SS with 1122SS Stainless Steel 2" Flat Super Air Nozzle .015" (0.38mm) shim installed


resistance.

Ozs Grams

624



b.				
P	۱			
	þ			
_				
G	ш	ın		



M SLPM lbs Grams dBA Use Mg 9075' Coiled	01	nsumption	Fo	rce*	Sound Level	
991 1.9 850 82 Coiled	1	SLPM	lbs	Grams	dBA	Use Mo 90075
		991	1.9	850	82	Coiled

Nozzle: 1104 3/8 NPT Super Air Nozzle

1122 2" Flat

Super Air Nozzle

Also Available: 1350SS with 1104SS 3/8 NPT Stainless Steel Super Air Nozzle 1350-PEEK with 1104-PEEK 3/8 NPT PEEK Plastic Super Air Nozzle



Air Consumption		For	Sound Level	
SCFM	SLPM	lbs	Grams	dBA
37	1,039	2.2	1,134	83

#### Nozzle:

HP1125 2" High Power Flat Super Air Nozzle

#### Also Available:

HP1330SS with HP1125SS Stainless Steel 2" High Power Flat Super Air Nozzle ₩ .025" (0.64mm) shim installed



Air Cons	umption	Fo	rce*	Sound Level
SCFM	SLPM	lbs	Grams	dBA
56	1,585	3.2	1,451	82

#### Model 1340 HD Safety Air Gun Nozzle:

1111-4 Super Air Nozzle Cluster



Air Consumption		Force*		Sound Level
SCFM	SLPM	lbs	Grams	dBA
60	1,699	3.3	1,497	87

Nozzle: 1106 1/2 NPT Super Air Nozzle

Also Available: 1360SS with 1106SS 1/2 NPT Stainless Steel Super Air Nozzle



Air Consumption		Sound Level	Use With:
SCFM	SLPM	dBA	Inside Diameter
22	622	80	7/8"-4" (22-102mm)

#### Model 1306SS-X-CS HD Back Blow Safety Air Gun

1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension, and Chip Shield

\*Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).

#### **Add An Extension Pipe**

Add an Extension Pipe to your Heavy Duty Safety Air Gun. Here's how:


- 1. Choose an EXAIR Heavy Duty Safety Air Gun. Example: Model 1310
- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length after the model of the Heavy Duty Safety Air Gun. (See table below)


**Example:** The Model 1310 Heavy Duty Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1310-12.

#### **Aluminum Extension Pipe** All Heavy Duty Safety Air Guns with

Extension Pipes come fully assembled.

Model Addition # / Extension Length					
-6	6" (152mm)				
-12	12" (305mm)				
-18	18" (457mm)				
-24	24" (610mm)				
-36	36" (914mm)				
-48	48" (1219mm)				
-60	60" (1524mm)				
-72	72" (1829mm)				













### **Back Blow Safety Air Guns**



#### Back Blow Safety Air Guns - 1/4, 3/8 and 1 NPT Inlet

Back Blow Safety Air Guns are perfect for cleaning out the inside of pipe, tube, hose or channels. EXAIR's engineered back blow nozzle provides a powerful 360 degree airflow through an array of holes to remove coolant, chips or debris. Available in our VariBlast, Soft Grip, Heavy Duty or Super Blast version, each gun style can be outfitted with an up to 72" extension to reach far into your application and provide airflow. VariBlast, Soft Grip and Heavy Duty Back Blow Safety Air Guns are outfitted with a Chip Shield to protect the operator from flying debris. Since airflow is directed back toward the operator, personal protection equipment is recommended.

#### Model 1604SS-X-CS VariBlast Compact Back Blow Safety Air Gun

Nozzle: 1004SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield

The VariBlast Compact Back Blow Safety Air Gun has dual 1/4 NPT inlets and provides a variable force trigger on a small, powerful and ergonomic air gun.

	Air Consumption		Sound Level	Use With:
Model	SCFM	SLPM	dBA	Inside Diameter
1604SS	4.5	127	75	1/4"-1" (6.3-25.4mm)

Model SCFM SLPM dBA Inside Diameter

Model	Description	Model	Description
1604SS-6-CS	VariBlast, 6" Extension, Chip Shield	1604SS-24-CS	VariBlast, 24" Extension, Chip Shield
1604SS-12-CS	VariBlast, 12" Extension, Chip Shield	1604SS-36-CS	VariBlast, 36" Extension, Chip Shield

#### Model 1204SS-X-CS Soft Grip Back Blow Safety Air Gun Nozzle:

1004SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield

#### The Soft Grip Back Blow Safety Air Gun

provides an ergonomic design with a 1/4 NPT

inlet and a fi	1204SS	4.5	127	75	1/4"-1" (6.3-25.4mm)	
nours or con	tinuous operation without fatigue.					
Model	Description	Model		D	escripti	ion
120455-6-05	Soft Grin 6" Extension Chin Shiold	120455-24-05	Soft Cri	n 24" Ev	toncion	Chin Shiold



1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield

#### The Soft Grip Back Blow Safety Air Gun

1204SS-12-CS Soft Grip, 12" Extension, Chip Shield

provides an ergonomic design with a 1/4 NPT inlet and a full grip trigger which is ideal for hours of continuous operation without fatigue.

		lir mption	Sound Level	Use With:
Model	SCFM	SLPM	dBA	Inside Diameter
1206SS	22	622	80	7/8"-4" (22-102mm)

622 80

1204SS-36-CS Soft Grip, 36" Extension, Chip Shield

Model	Description	Model	Description
1206SS-6-CS	Soft Grip, 6" Extension, Chip Shield	1206SS-36-CS	Soft Grip, 36" Extension, Chip Shield
1206SS-12-CS	Soft Grip, 12" Extension, Chip Shield	1206SS-48-CS	Soft Grip, 48" Extension, Chip Shield
1206SS-18-CS	Soft Grip, 18" Extension, Chip Shield	1206SS-60-CS	Soft Grip, 60" Extension, Chip Shield
1206SS-24-CS	Soft Grip, 24" Extension, Chip Shield	1206SS-72-CS	Soft Grip, 72" Extension, Chip Shield



Nozzle:

Extension

1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield

The Heavy Duty Back Blow Safety Air Gun has a larger rubber grip and a larger 3/8 NPT inlet upon a durable cast aluminum gun body and full orin trigger to ease fatigue

and run grip	trigger to ease ratigue.		
Model	Description	Model	Description
1306SS-6-CS	Heavy Duty, 6" Extension, Chip Shield	1306SS-36-CS	Heavy Duty, 36" Extension, Chip Shield
1306SS-12-CS	Heavy Duty, 12" Extension, Chip Shield	1306SS-48-CS	Heavy Duty, 48" Extension, Chip Shield
1306SS-18-CS	Heavy Duty, 18" Extension, Chip Shield	1306SS-60-CS	Heavy Duty, 60" Extension, Chip Shield

Model SCFM SLPM dBA

130655

1306SS-24-CS Heavy Duty, 24" Extension, Chip Shield 1306SS-72-CS Heavy Duty, 72" Extension, Chip Shield

Super Blast Back Blow Safety Air Guns provide the strongest blowing force to remove debris from the largest pipe diameters and deepest channels. These guns are sold with a 1', 3' and 6' extension, a comfortable soft grip and a spring-loaded manual valve which



Safety Air Gun

Nozzle: 1008SS Stainless Steel Back Blow Air Nozzle and Aluminum


1219SS Super Blast, 1' (305mm) Extension 1219SS-3 Super Blast, 3' (1m) Extension 1219SS-6 Super Blast, 6' (1.8m) Extension

will shut off automatically if it is dropped.

		Consu	lir mption	Sound Level	Use With:
+	Model	SCFM	SLPM	dBA	Inside Diameter
	1219SS	57	1,614	89	2"-16" (51-406mm)



Model



Description

Inside Diameter

7/8"-4"

(22-102mm)

#### **High Force Safety Air Guns**

These hand-held versions of our Super Air Nozzle Clusters and large Super Air Nozzles provide the same strong blowing force with the added convenience of a comfortable soft grip and easy to operate spring-loaded manual valve that automatically shuts off if it is dropped. The Super Blast Safety Air Guns are ideal for long distance, wide area blowoff, cooling and drying applications. All Super Blast Safety Air Guns meet OSHA noise level and pressure requirements.



#### Add a longer extension pipe to your Super Blast Safety Air Gun.

Create the model number by adding a dash and number of the extension pipe to the Super Blast Safety Air Gun.

#### **Example:**

The Model 1213-4 Super Blast Safety Air Gun with a 3' extension would be a Model 1213-4-3.

1213-4 (Super Blast Safety Air Gun) -3 (3' extension)

1213-4-3

#### **Aluminum Extension Pipe** All Super Blast Safety Air Guns with Extension Pipes come fully assembled.

Model#	Model Addition# / Extension Length				
1213-4	-3	36" (914mm)			
3/8 NPT	-6	72" (1829mm)			
1213-7	-3	36" (914mm)			
1/2 NPT	-6	72" (1829mm)			
1213-12	-3	36" (914mm)			
1 NPT	-6	72" (1829mm)			


#### Super Blast Safety Air Gun™



Model 1213-4 3/8 NPT female Material: Nozzles - Zinc Aluminum alloy Body - Aluminum

Airflow Pattern: see Model 1111-4 on page 65.






Air Consumption		Force*		Sound Level
SCFM	SLPM	lbs	Kg	dBA
56	1,585	3.2	1.45	82

<sup>\*</sup> Force measured at 12" (305mm) from target Sound level measured at 3' (914mm All measurements taken at 80 PSIG (5.5 BAR)



Model 1213-7 1/2 NPT female Material: Nozzles - Zinc Aluminum alloy Body - Aluminum

Airflow Pattern: see Model 1111-7 on page 65.




Air Cons	umption	For	ce*	Sound Level
SCFM	SLPM	lbs	Kg	dBA
98	2,773	5.7	2.59	85

\* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)



Model 1213-12 1 NPT female Material: Nozzles - Zinc Aluminum alloy Body - Aluminum

Airflow Pattern: see Model 1111-12 on page 65. DOWNLOAD



onsumption Force* Soun Leve		Sound Level	
SLPM	lbs	Kg	dBA
4,754	9.8	4.45	89
		SLPM lbs	SLPM lbs Kg

\* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)









#### Super Blast Safety Air Gun™




Model 1214 3/4 NPT female

Material: Nozzles - Zinc Aluminum alloy

Airflow Pattern: see Model 1112 on page 63.

**Airflow Pattern:** see Model 1112 on page 63. **Model 1214SS** with Stainless Steel Nozzle also available




Air Consumption		For	Sound Level	
SCFM	SLPM	lbs	Kg	dBA
91	2,577	4.5	2.04	96

\* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR) OSHA 3 hour total exposure per day without hearing protection



Model 1215 1 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1114 on page 63. Model 1215SS with Stainless Steel Nozzle also available



Air Consumption		For	Sound Level	
SCFM	SLPM	lbs	Kg	dBA
135	3,823	6.6	3.01	99
F Faces and a state of the stat				

Sound level measured at 3' (914mm)
All measurements taken at 80 PSIG (5.5 BAR)
OSHA 2 hour total exposure per day without hearing protection



The 3' extension on the Model 1215-3 Super Blast Safety Air Gun helps an operator provide maximum blow off force to remote, tight or difficult to access areas.



Model 1216 1-1/4 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1116 on page 64.



Model 1217 1-1/4 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1118 on page 64.



Model 1218 1-1/4 NPT female

Material: Nozzle - Zinc Aluminum alloy

Airflow Pattern: see Model 1120 on page 64.



Model	Consumption		Force*		Level
	SCFM	SLPM	lbs	Kg	dBA
1216	188	5,324	9.4	4.25	102
1217	300	8,495	15	6.80	106
1218	460	13,026	23	10.43	109

\* Force measured at 12" (305mm) from targ Sound level measured at 3' (914mm)

All measurements taken at 80 PSIG (5.5 BAR)

Model 1216 OSHA 1 hour total exposure per day without

hearing protection

Model 1217 and 1218 OSHA ½ hour total exposure per day

without hearing protection

# Add a longer extension pipe to your Super Blast Safety Air Gun.

Create the model number by adding a dash and number of the extension pipe to the Super Blast Safety Air Gun.

#### Example:

The Model 1214 Super Blast Safety Air Gun with a 3' extension would be a Model 1214-3.

1214 (Super Blast Safety Air Gun)
-3 (3' extension)

1214-3

Aluminum Extension Pipe				
All Super Blast Safety Air Guns with Extension Pipes come fully assembled.				
Model# Model Addition # / Extension Length				
1214	-3	36" (914mm)	-6	72" (1829mm)
1214SS	-3	36" (914mm)	-6	72" (1829mm)
1215	-3	36" (914mm)	-6	72" (1829mm)
1215SS	-3	36" (914mm)	-6	72" (1829mm)
1216	-3	36" (914mm)	-6	72" (1829mm)
1217	-3	36" (914mm)	-6	72" (1829mm)
1218	-3	36" (914mm)	-6	72" (1829mm)



### **EXAIR** Standards Compliance

As the leader in standards compliance, EXAIR's products come with more than engineered performance, peak efficiency, the best technical knowledge and unmatched customer service....

EXAIR is dedicated to providing products that have been manufactured to meet the strict requirements of the following standards. These standards provide confidence that you are receiving reliable, high quality products which will perform as stated within the performance charts provided.

Our products meet or exceed the strict safety standards of OSHA and the European Union to ensure the safety of your personnel. Many of these standards will allow your products a smoother transaction when selling your products into international markets.

#### OSHA and CE Compliance:



EXAIR compressed air products comply with OSHA's Safety Requirements (29 CFR 1910.242(b)), the EU General Product Safety Directive (2001/95/EC) and meet the noise limitation requirements (29 CFR-1910.95(a)), of the EU Machinery Directive (2006/42/EC). EXAIR's Electronic Flow Control and Electronic Temperature Control meet the low voltage standards of the EU Low Voltage Directive (2006/95/EC). Some EXAIR products display the CE mark where there are applicable directives. All sound level measurements are taken at 3 feet from product.



Electrical portions of EXAIR's Static Eliminators, EFC, ETC, Digital Flowmeter solenoid valves, and thermostats comply with the RoHS (Restriction of Hazardous Substances) Directive 2011/65/EU, including the amendment outlined in the European Commission decision L 214/65.

#### Conflict Mineral Free:



Look for this symbol to designate conflict mineral free products throughout our catalog. EXAIR supports Section 1502 of the Dodd-Frank Wall Street Reform and Consumer Protection Act. We are committed to compliance with the conflict minerals rule in order to curb the illicit trade of tin, tantalum, tungsten and gold in the DRC region. EXAIR is using the CMRT 4.20 template to document our supply chain and commitment to conflict free products.



Per Regulation (EC) No 1907/2006 Title I, Article 3, paragraph 3, the European Union has recently enacted legislation to register chemicals and substances imported into the EU to ensure a high level of protection of human health and the environment.

Per Title II, Article 7, paragraph 1, articles (products) must be registered when a substance is intended to be released under normal or reasonably foreseeable conditions of use and it is present in those articles in quantities totaling over 1 metric ton per producer or importer per year. Registration of EXAIR products is not required since they do not contain substances that are intentionally released.





